

Product Data Sheet

FT-10 FUEL TREATMENT™

For Fuel Oil Furnaces/Boilers & Fuel Storage Tanks

General Information

- Blends with all types of fuel
- A blend of high-quality, petrochemical products
- Contains MPC's MT-10 Metal Treatment™ & other superior additives

Key Features & Benefits

- Provides better fuel-air mix, increasing combustion of fuel & fuel efficiency
- Disperses water & moisture in fuel & uniformly combusts with fuel
- Provides fuel pump lubrication, extending pump life
- Cleans furnace's combustion system during operation
- Cleans nozzles & pump systems
- Dissolves & removes gum deposits from fuel lines
- Inhibits formation of fuel gums & resins
- Protects the fuel system from rust & corrosion
- Inhibits fungi & bacteria build up in the fuel
- Improves furnace performance
- Reduces harmful emissions
- Reduces fuel consumption
- Reduces jelling & waxing
- Reduces soot & carbon

Typical Applications

- Fuel oil furnaces & boilers
- Fuel storage tanks
- Also recommended for automotive gasoline & diesel engines

Availability

- 2-oz. & 16-oz. bottles
- 1-gallon & 5-gallon containers
- 15-gallon & 55-gallon drums
- Tote bins & larger bulk containers upon request

Directions for Use

General: For best results, add FT-10 to the fuel tank prior to refueling. FT-10 will easily blend with the fuel oil.

Furnaces/Boilers: Add 2 oz. of FT-10 for every 10 gallons of fuel.

Bulk Fuel Storage Tanks: Add 2 oz. of FT-10 for every 10 gallons of fuel.

Typical Properties

Appearance Light green liquid
Odor Alcohol type
Viscosity 2.29 cSt @ 40°C (104°F)
Freezing Point..... Not established
Melting Point..... Not applicable
Boiling Point 176°F (80°C)
Flash Point 45°F (7.2°C) closed cup
Autoignition Temperature... ~ 750°F (399°C)
Evaporation Rate (nBuAc = 1)..... ~ 1.5
Vapor Pressure 1.125 PSI
Vapor Density (Air = 1) ~ 2
Specific Gravity @ 60°F 0.8012 g/cm³
Solubility in Water Partially
VOC Content Not established

Health & Safety Hazards

WARNING! Causes eye irritation. Avoid eye contact. May cause skin irritation. Avoid prolonged contact with skin. Use with adequate ventilation.

WARNING! Flammable liquid and vapor. Keep away from heat, sparks and flame.

See Material Safety Data Sheet for additional information.

U.S. DOT Freight Classification

- Identification Number: UN 1993
- Proper Shipping Name: Flammable Liquid, n.o.s. (isopropanol)
- Hazard Class: 3
- Packing Group: II



“The Strength in Lubrication”[®]

752 Kilgore Road

Jackson Center, PA 16133 U.S.A.

Phone: 800-227-7049

814-786-0166

Fax: 814-786-7321

Website: www.mpclubricants.com