

Product Data Sheet

FT-10 FUEL TREATMENT™

For Gasoline & Diesel Engines

General Information

- Recommended for both gasoline & diesel engines
- Complies with federal sulfur content requirements for use in diesel engines
- Blends with all grades of leaded & unleaded gasoline
- A blend of high-quality, petrochemical products
- Contains MPC's MT-10 Metal Treatment™ & other superior additives

Key Features & Benefits

- Increases atomization in carburization & fuel injection
- Reduces harmful emissions
- Cleans entire fuel system
- Assists in neutralizing combustion acids
- Improves mileage
- Blasts upper cylinder carbons
- Provides upper cylinder lubrication
- Disperses water in the fuel
- Controls algae, jelling & waxing in diesel engines
- Provides quicker starts in cold temperatures
- Enhances overall engine performance

Typical Applications

- Gasoline engines
- Diesel engines
- 2-cycle engines
- 4-cycle engines
- Also recommended for bulk fuel storage tanks

Availability

- 2-oz. & 16-oz. bottles
- 1-gallon & 5-gallon containers
- 15-gallon & 55-gallon drums

Directions for Use

General: For best results, add FT-10 to the fuel tank prior to refueling. FT-10 will easily blend with the fuel.

Gasoline & Diesel Engines: For initial treatment, add 2 oz. of FT-10 for every 10 gallons of fuel. For follow-up treatments, add 1 oz. of FT-10 for every 10 gallons of fuel. Add to the fuel tank at every fill up.

In temperatures below 32°F (0°C), continue using 2 oz. of FT-10 for every 10 gallons of fuel.

2 & 4-Cycle Engines: Add 2 oz. of FT-10 to 5 gallons of fuel. For high-performance engines, add 4 oz. of FT-10 to 5 gallons of fuel.

Note for 2-cycle engines: Be sure to continue using the oil mixture as recommended by the equipment manufacturer.

Typical Properties

Appearance Light green liquid
Odor Alcohol type
Viscosity 2.29 cSt @ 40°C (104°F)
Freezing Point..... Not established
Melting Point..... Not applicable
Boiling Point 176°F (80°C)
Flash Point 45°F (7.2°C) closed cup
Autoignition Temperature... ~ 750°F (399°C)
Evaporation Rate (nBuAc = 1)..... ~ 1.5
Vapor Pressure 1.125 PSI
Vapor Density (Air = 1) ~ 2
Specific Gravity @ 60°F 0.8012 g/cm³
Solubility in Water Partially
VOC Content Not established

Health & Safety Hazards

WARNING! Causes eye irritation. Avoid eye contact. May cause skin irritation. Avoid prolonged contact with skin. Use with adequate ventilation.

WARNING! Flammable liquid and vapor. Keep away from heat, sparks and flame.

See Material Safety Data Sheet for additional information.

U.S. DOT Freight Classification

- Identification Number: UN 1993
- Proper Shipping Name: Flammable Liquid, n.o.s. (isopropanol)
- Hazard Class: 3
- Packing Group: II



"The Strength in Lubrication"[®]

752 Kilgore Road

Jackson Center, PA 16133 U.S.A.

Phone: 800-227-7049

814-786-0166

Fax: 814-786-7321

Website: www.mpclubricants.com