

## Product Data Sheet

### MO-10 MOIST-OUT™

#### General Information

- Demoisturant, light lubricant, penetrant & rust inhibitor – all in one product
- A blend of high-quality, petrochemical products
- Contains MPC's MT-10 Metal Treatment™ for enhanced lubrication qualities
- Contains no PTFE, silicone, graphite, moly or solid lubricants

#### Key Features & Benefits

- Prevents rust & corrosion
- Quick, thorough moisture displacement
- Does not contain carbon tetrachloride & will *not* harm insulation
- Long-lasting lubrication
- Creeps into remote, inaccessible areas
- Loosens scale & frees up frozen metal mechanisms
- Provides free-flowing protection

#### Typical Applications

- **Demoisturant:** Wet or damp ignitions, electrical circuits, motors, controls, starters, relays, radios, electronic equipment, etc. CAUTION: Never spray any demoisturant on a live circuit. Serious shock or injury may occur.
- **Light lubricant:** Metal mechanisms, gears, locks, linkage, wheel bearings, metal-to-metal moving or sliding surfaces, guns, cams, levers, engines, motors, slides, hinges, industrial equipment, etc.
- **Penetrating oil:** Rusty lugs or bolts, sluggish mechanisms, sliding parts, hinges, tools, products in storage, gear trains, wheels, rotating apparatus, linkage, cams, levers, industrial equipment, etc.

- **Anticorrosive rust inhibitor:** Rusty parts & mechanisms, storage items to prevent rust, industrial equipment, & all previously mentioned areas of applications

#### Availability

- 16-oz. plastic bottles\*
  - 1-gallon & 5-gallon containers
  - 15-gallon & 55-gallon drums
- \* Trigger (pump) sprayers sold separately

#### Typical Properties

Boiling Point .....	> 380°F
Flash Point .....	> 230°F PMCC
Specific Gravity @ 60°F .....	0.9095
Vapor Density (Air = 1) .....	> 5.0
Vapor Pressure (mm Hg) @ 20°C .....	0.01
Evaporation Rate (Butyl Acetate=1) ...	1000 times slower than ethyl ether
Timken Extreme Pressure OK Load .....	60+
Pour Point .....	- 48°F
Odor .....	Mild petroleum
Color .....	Green
Appearance .....	Low viscosity liquid
Dielectric strength .....	< 45 KV
Antirust corrosion inhibitor .....	Yes
Solubility in Water .....	Insoluble

#### Material Safety Data

- **Ingestion:** Do not induce vomiting. Call a physician immediately.
- **Eye Contact:** Flush with water for 15 minutes. Call a physician if irritation persists.
- **Skin Contact:** Wash thoroughly with soap & water. Call a physician if irritation occurs.

- **Storage:** Do not store in temperatures above 130°F. Keep away from sparks & open flames.
- For additional information, please refer to Material Safety Data Sheet (MSDS).

Freight Classification

- **Classification:** Lubricant Oil
- **Hazard Class:** Nonhazardous
- **Packing Group:** N/A



***“The Strength in Lubrication”***<sup>®</sup>

752 Kilgore Road  
Jackson Center, PA 16133  
Phone: 800-227-7049  
814-786-0166  
Fax: 814-786-7321  
Website: [www.mpclubricants.com](http://www.mpclubricants.com)