

## Product Data Sheet

### SL-10 OIL CAN LUBRICANT™

#### Heavy Duty Spray Lubricant

##### General Information

- A blend of high-quality, petrochemical products
- Contains MPC's MT-10 Metal Treatment™ & PL-10 Power-Lift Grease™ for enhanced lubrication qualities
- Contains no PTFE, silicone, graphite, moly or solid lubricants

##### Key Features & Benefits

- Long-lasting protection against rust & corrosion
- Protects against extreme humidity environments
- Quick lubricating & penetrating action
- Creeps into remote, inaccessible areas
- Provides free-flowing protection

##### Typical Applications

- Metal mechanisms
- Sleeve bearings
- Metal-to-metal surfaces
- Open gears
- Chain drives
- Steel cables
- Drag lines
- Couplings
- Bushings
- Linkages
- Pulleys
- Wheels
- Hinges
- Augers
- Tools

- Any automotive, industrial or commercial areas of lubrication that require an external spray lubricant for accessible or hard-to-reach areas

##### Availability

- 16-oz. plastic bottles\*
  - 1-gallon & 5-gallon containers
  - 15-gallon & 55-gallon drums
- \* Trigger (pump) sprayers sold separately

##### Directions for Use

Shake container well. Wipe off exposed surfaces; apply SL-10 Oil Can Lubricant™ directly to areas to be lubricated. Repeat in especially stubborn applications.

##### Typical Properties

Boiling Point .....	> 380°F
Flash Point .....	230°F PMCC
Specific Gravity @ 60°F .....	0.94
Vapor Density (Air = 1) .....	> 5.0
Vapor Pressure (mm Hg) @ 20°C .....	0.01
Evaporation Rate (Butyl Acetate=1) ...	< 0.01
Viscosity (SUS) .....	< 100
Timken Extreme Pressure OK Load .....	60+
Pour Point .....	- 32°F
Odor .....	Mild petroleum
Color .....	Milky amber
Appearance .....	Low viscosity liquid
Antirust corrosion inhibitive .....	Yes
Water resistant .....	Yes
Solubility in Water .....	Insoluble

## Material Safety Data

- **Ingestion:** Do not induce vomiting. Call a physician immediately.
- **Eye Contact:** Flush with water for 15 minutes. Call a physician if irritation persists.
- **Skin Contact:** Wash thoroughly with soap & water. Call a physician if irritation occurs.
- **Storage:** Do not store in temperatures above 130°F. Keep away from sparks & open flames.
- For additional information, please refer to Material Safety Data Sheet (MSDS).

## Freight Classification

- **Classification:** Lubricant Oil
- **Hazard Class:** Nonhazardous
- **Packing Group:** N/A



***“The Strength in Lubrication”***<sup>®</sup>

752 Kilgore Road  
Jackson Center, PA 16133

Phone: 800-227-7049

814-786-0166

Fax: 814-786-7321

Website: [www.mpclubricants.com](http://www.mpclubricants.com)